



**60840—
2017**

30 ($U_m = 36$) 150 ($U_m = 170$)

(IEC 60840:2011,)



2017

60*40—2017

1
2
3
4

« , »)
46 « »
19 1 1147-
60840:2011 « 30 { $U_m = 36$ })
150 ($U_m - 170$). » (IEC 60840:2011 «Power cables with ex-
truded insulation and their accessories for rated voltages above 30 kV ($U_m - 36$ kV) up to 150 kV ($U_m - 170$ kV). Test methods and requirements». IDT).

5 60840—2011

⁶ , 4.

€ , 2017

1	1	
2	1	
3	3	
3.1	(.. .) ..	3	
3.2	, ..	3	
3.3	4	
4	4	
4.1	4	
4.2	4	
4.3	/ ..	4	
4.4	4	
5	4	
6	5	
7	5	
8	6	
8.1	6	
8.2	6	
8.3	(..) ..	6	
8.4	6	
8.5	6	
9	- ..	6	
9.1	6	
9.2	7	
9.3	7	
9.4	7	
10	7	
10.1	7	
10.2	8	
10.3	8	
10.4	8	
10.5	8	
10.6	8	
10.7	9	
10.8	10	
10.9	(XLPE), (HEPR)	(EPR)	10
10.10	10	
10.11	(HDPE).....	10
10.12	10	
10.13	10	
10.14	,	11

60*40—2017

11	11
11.1	11
11.2	11
12	11
12.1	11
12.2	11
12.3	12
12.4	13
12.5	15
13	19
13.1	...	19
13.2	20
13.3	,	
	22
14	24
14.1	24
14.2	24
14.3	24
14.4	25
15	25
15.1	25
15.2	25
15.3	26
15.4	26
16	27
16.1	27
16.2	27
16.3	27
()	,	
()	33
()	,	
	,	
	37
D()	39
()	41
F()	,	
	43
G()	45
()	47
()	49
	51

$$8 \quad 30 \quad (U_m \ll 36) \quad 150 \quad (U_m \ll 170)$$

Power cables with extruded insulation and their accessories for rated voltages above 30 kV ($U_m = 36$ kV) up to 150 kV ($V_m = 170$ kV). Test methods and requirements

— 2010—01—01

1

$$30 \quad (U_m - 36) \quad 150 \quad [U_m = 170]$$

2

8

60811,

8 60811-100.

IEC 60060-1, High-voltage test techniques — Part 1: General definitions and test requirements (.)
1.

IEC 60183, Guide to the selection of high-voltage cables () no

IEC 60228. Conductors of insulated cables (

IEC 60229. Electric cables — Tests on extruded oversheaths with a special protective function (

IEC 60230. Impulse tests on cables and their accessories (

IEC 60287-1-1:2006. Electric cables — Calculation of the current rating — Part 1-1: Current rating equations (100 % load factor) and calculation of losses — General (

60*40—2017

IEC 60332-1-2. Tests on electric and optical fibre cables under fire conditions — Part 1-2: Test for vertical flame propagation for a single insulated wire or cable — Procedure for 1 kW pre-mixed flame (

1-2.

1

)

IEC 60811-1-1:19934 Common test methods for insulating and sheathing materials of electric and optical cables — Section 1-1: Methods for general application — Measurement of thickness and overall dimensions — Tests for determining the mechanical properties. Amendment 1 (2001) (

1-1.

)

IEC 60811-1-2:19854 Common test methods for insulating and sheathing materials of electric cables — Part 1: Methods for general application — Section 2: Thermal ageing methods. Amendment 1 (1989). Amendment 2 (2000) (

1. 2.)

IEC 60811-1-3:19934 Common test methods for insulating and sheathing materials of electric cables — Part 1-3: General application — Methods for determining the density — Water absorption tests — Shrinkage test. Amendment 1 (2001) (

1-3.

)

IEC 60811-1-4:1985⁴¹. Common test methods for insulating and sheathing materials of electric cables — Part 1: Methods for general application — Section 4: Tests at low temperature. Amendment 1 (1993). Amendment 2 (2001) (

1. 4.)

IEC 60811-2-1:19984 Common test methods for insulating and sheathing materials of electric and optical cables — Part 2-1: Methods specific to elastomeric compounds — Ozone resistance, hot set and mineral oil immersion tests. Amendment 1 (2001) (

2-1.

)

IEC 60811-3-1:1985⁴¹. Common test methods for insulating and sheathing materials of electric cables — Part 3: Methods specific to PVC compounds — Section 1: Pressure test at high temperature — Tests for resistance to cracking. Amendment 1 (1994), Amendment 2 (2001) (

3.

1.

)

IEC 60811-3-2:1985⁴¹. Common test methods for insulating and sheathing materials of electric cables — Part 3: Methods specific to PVC compounds — Section 2: Loss of mass test — Thermal stability test. Amendment 1 (1993). Amendment 2 (2003) (

3.

2.)

IEC 60811-4-1:20044 Insulating and sheathing materials of electric and optical cables — Common test methods — Part 4-1: Methods specific to polyethylene and polypropylene compounds — Resistance to environmental stress cracking — Measurement of the melt flow index — Carbon black and/or mineral filler content measurement in polyethylene by direct combustion — Measurement of carbon black content by thermo gravimetric analysis (TGA) — Assessment of carbon black dispersion in polyethylene using a microscope) (

4-1.

60811. 201—203. 501.

2> 60611. 401.412.

3) 60811. 402. 502, 503, 606.

60611. 504—506.

s> 60611. 403.404, 507.

> 60811. 508. 509.

?) 60811. 405.409.

3) 60611. 406. 511. 605.

2

(TGA).

1

*
六

IEC 60885-3. Electrical test methods for electric cables — Part 3: Test methods for partial discharge measurements on lengths of extruded power cables (

3.

)

ISO 48. Rubber, vulcanized or thermoplastic — Determination of hardness (hardness between 10IRHD and 100 IRHD) (10-100 IRHD)

3

6

3.1

(, , ,)

3.1.1

(nominal value):

312

(median value):

()

32

321

(routine tests):

322

(sample tests):

323

(type tests).

3.2.4

(prequalification tests):

3.2.5 , (extension of prequalification tests):

326

(electrical tests after installation):

60*40—2017

3.3

3.3.1

(cable system):

3.3.2

 U_0

(nominal electrical stress):

4

4.1

 U_0, U, U_m

60183.

4.2

1

4.3

/

4.4

- ST, ST₂
- ST₃ ST₇

2.

(,).

5

12.5.14.

4

6

a)

;

b) — U_0, U, U_m (.4.1 8.4);

c)

;

d) 60228,

1

20 ;

 (t_n) (. 4.2). $\operatorname{tg} 6$

;

e)

f)

)

;

h)

i)

j)

k)

l)

;

)

():

(d):

;

(^)

;

1

;

():

(1>)

 $2U_a$ $E \circ * 4 \ln (D_w / d_{rt})$

(2)

 $= d^* 2t,;$ $D_n —$ $d_u —$ $t, —$ U_0

4.

7

a)

6;

b)

•

•

•

•

•

;

5

60*40—2017

)
 . ; ;
 . , [. 6.];
 . (.).

8

8.1

(20 ± 15) »

8.2

49—61

8.3

60230
1—5
(SO 110) 60060-1.

8.4

, U_0
4.
 U_0 ,
 U_m
4., U_0 , U_1 , ^2.
,
8 60183.

8.5

9

9.1

a) 9.2:
b) 9.3;
c) () 9.4.

9.2 9.3

1), ;
2), ;

6

3)

2) 3)

9.2 9.3.

9.2

60885-3
60885-3.
10
510 1.5 U_Q (. 5 4).
1.5 ,

9.3

30

2.5 U_0
(. 4

4).

9.4

60229 (3).

10

10.1

- ,
- ,
-) 10.4;
-) 10.5:
- c) 10.6:
- d) 10.7:
- e) (10.8: (XLPE).
- 0 (EPR) 10.9;
-) 10.10;
- h) (HDPE) 10.11;
- i) > 8.0 / 6.
-). 10.12;
- j) () 10.13;
- k), 10.14.

60*40—2017

10.2

)—h) () 10.1
 10 %

i) j) 10.1

20

10.3

10.1

10.4

60226

()

10.5

12

24

1

20 *

1

60228.

60287-1-1 (2.1.1. 1).

20 *

60228.

20 °

10.6

10.6.1

60811-1-1 (8).

10.6.2

90 %

 $t \leq 0.90f_{cr}$

(3)

$$\frac{t_{\max} - t_{\min}}{t_{\max}} \leq 0,15, \quad (4)$$

$$\begin{aligned} f_{\max} - & \quad , \quad ; \\ 1L, - & \quad , \quad ; \\ t_n - & \quad , \quad . \\ - 1^{\wedge} & \end{aligned}$$

10.6.3

0.1

$$f_{min} \geq 0.85_{mm} - 0.1, \quad (5)$$

$$f_{\min} =$$

$$f_{\max} =$$

0.1

8.

10.7

10.7.1

95 %

0.1

$\text{mm}^* \quad L \cdot b 0.95 f - 0.1$ ()

10.7.1.1

4-8

$\pm 0,01$

50

10

10.7.12

0.8

2.4

+0.01

90 %

01

$$t_{\text{min}} \geq 0.9t_c - 0.1 \quad (7)$$

60*40—2017

85 % 0.1 *

 $L_{ta}S0.85f_e-0.1.$ (8)

3 — ±0,01 50

10.8

60811-1*1 (8.3).

10.9 (XLPE),
(EPR) (HEPR)10.9.1 — 60811*2*1 (9).
8.

10.9.2 8.

10.10

1
8 %.

10.11 ()

10.11.1 60811*1*3 (8). (HDPE)

10.11.2 8.

10.12

>8.0 / 10 , 5—10

10 10 60230.
8 4.

10.13

12.5.14.

10.14

12.5.15.

11

11.1

11.2

(. . 9.1),

a)
b)

9.2;
9.3.

50.

12

12.1

12.2

)—f):

8

11

60*40—2017

a)
();—
(. U_m 1 2 4).b)
c)

();

/).

d)

() 10 %;

e)
f)

().

12.5

/ /

12.5.4.

12.3

12.4

12.5.

5.

12.4.2

10

5

).

, , , (

, , ,).

12.4

12.4.1

60811-1-1 (8.1)

12.4.9

15 %,

5 %,
4

5 %.

12.4.2

>—h)

a)

12.4.3

12.4.4;

b)

12.4.5;

c)

12.4.6:

d)

12.4.4:

•

•

e)

12.4.7;

f)

d);

g)

G;

h)

},

G.

i)

12.4.8;

12.4.9.

4.

12.4.3

) 180

60*40—2017

• $36(4+D) \quad 5\% —$
 • $25(d+) \quad 5\% —$
 • $2S(d+D) + 5\% —$
 • $20(d+D) \quad 5\% —$
 • $20(d+D) \quad 5\% —$
 • $15(d+D) + 5\% —$
 d— , [. i). 6].
 D— , [. j). 6].
 —

12.4.4

60885-3.

5

10 . $1.5U_0(. \quad 5 \quad 4).$ 1.75 ,

5—10

2

 $1.5U_0$

12.4.5

S—10 *

12.4.6

tg 5
 (. 6 4). U_Q
 tg 5

3.

12.4.3.

5—10 ®

1

2

10 *

8
2
16
10 *
30 *

20
20

$2U_0$ (. . .)

7 4).

12.4.7

5—10 °

2 . . . ,

60230.
10 10

8 4.

2.5(J_0) 15 . . . 9 4.

12.4.8

12.4.8.1

(. . . , . . .),

12.4.8.2

1 12.5.15.

12.4.9

12.5.4.

12.4.9.1

 $\pm 2^*$

12.4.9.2

- — 1000
- — 500

12.5

a)

12.5.1:

b)

12.5.2:

60*40—2017

- c) 12.5.3;
- d)
- 12.5.4;
- e) (PVC)
- ST₂ 12.5.5;
- f) 12.5.6;
(PVC) ST, ST₂
-) 12.5.7;
- h) (PVC) ST, ST₂
- 12.5.8;
- i) (EPR)
- (HEPR) 12.5.9;
- j) (EPR). *
- (HEPR) (XLPE) 12.5.10;
- k) (HDPE) 12.5.11;
- l) () ST_a ST₇
- 12.5.12;
-) 12.5.13;
-) 12.5.14; *
-) 12.5.15;
-) , (), (HDPE)
- (XLPE) 12.5.16;
- q) () ST₃ ST₇ 12.5.17;
(HEPR)
- 12.5.18;
- s)
- (HEPR) 12.5.19.
- 12.5.1
- ,
- 10.4,10.6 10.7.
- 12.5.2
- 12.5.2.1
- 60811-1-1 (9.1).
- 12.5.2.2
- 60811-1-2 (8.1), -
- 6.
- 12.5.2.3
- 60811-1-1 (- 9.1).
- 12.5.2.4
- ,
- 6.
- 12.5.3
- 12.5.3.1
- 60811-1-1 (9.2).
- 12.5.3.2
- 60811-1-2 (8.1), -
- 7.
- 12.5.3.3
- 60811-1-1 (- 9.2).
- 12.5.3.4
- ,
- 7.

12.5.4

12.5.4.1

12.5.4.2

60811-1-2 (8.1.4).

12.5.4.3

60811-1-2 (8.1.4)

(10 ± 2) *

1;

—7

12.5.4.4

(8.1.4).

12.5.4.5

60811-1-2

(. 12.5.2 12.5.3),

6

7 —

12.5.5

(PVC) ST₂

12.5.5.1

ST₂

60811-3-2

(8.2)

9.

12.5.5.2

9.

12.5.6

12.5.6.1

ST_V ST₂ST₇

60811-3-1 (

8.2)

7.

12.5.6.2

60811-3-1 (

8.2).

(PVC)

12.5.7

ST, ST₂

12.5.7.1

ST, ST₂

60811-1-4

(8).

9.

12.5.7.2

60811-1-4 (8).

(PVC)

12.5.8

ST, ST₂

12.5.8.1

ST, ST₂

—

60811-3-1 (

9.2),

9.

12.5.8.2

60811-3-1 (9.2).

(EPR)

12.5.9

(HEPR)

60*40—2017

12.5.9.1		(EPR)			
(HEPR)				—	
60811-2*1 (6).			8.	
12.5.9.2					
12.5.10		60811*2*1 (8).		*
(HEPR)	(XLPE)	(EPR),			
(HEPR)	(XLPE)			10.9.	
12.5.11		(HDPE)	()	10.11.	
12.5.12					()
ST ₃ ST ₇					
12.5.12.1		ST ₃	ST ₇	60811*4*1 (*
11).					
12.5.12.2		(2.5 ± 0.5) %.			
12.5.13		60332*1 *2.			*
12.5.14		60332-1*2.			
12.5.15					
a)	— F.1,	F:			
b)		— F.2.	F;		
c)			,		
F.3.	F.				
12.5.16		F.			
(XLPE)		(),		()	
12.5.16.1					
(XLPE)		(),	60811*1*3 ((HDPE)	*
8.			10);		
12.5.16.2					
12.5.17		8.			
12.5.17.1		()	ST ₃ ST ₇		
(10);	—	7.		80811 *1 *3	
12.5.17.2					

60840—2017

12.5.18

(HEPR)

12.5.18.1

12.5.18.2

8.

12.5.19

(HEPR)

12.5.19.1

60811-1-1 (9).

150-

150-

12.5.19.2.

8.

13

13.1

8.0 8/ /

—4.0 / .

•

•

•

•

•

13.2.

13.3.

60*40—2017

1

(,
).

2

, ,

3

, ,

, ,

, ,

13.2

13.2.1

, ,

20

10 . :

a)

13.2.4:

b)

13.2.5;

c)

13.2.6.

, ,

13.2.

().

13.2.

, ,

13.2.

13.2.2

12.4.1.

13.2.3

, ,

). (

, ,

, ,

1.

, ,


U-

12.4.3.

, ,


1.

, ,



13.2.4

0—5 °



1

2

3

4

10

5 *

13.2.5

10

0—5 *

2

1

2

60*40—2017

60230.

6

4.
13.2.6

12.4.8.

13.3

13.3.1

12.5.

13.3.2

13.3.2.1

13.3.2.3

13.3.2,

20


S

).
)
,

U-
13.3.2.2

2.

12.4.3.
13.3.2.3,



2—

12.4.9

13.3.2.2

12.4.1.

13.3.2.3

- a) 12.4.3
- 12.4.4 ;
- b) 12.4.4 ;
- c) 13.3.2.4;
- d) 12.4.5;

e) 12.4.6:
0 12.4.4:

•

•

)

);

)

12.4.7;

h)
i));
G:

1

),

G.

2

{ G.3 G.4.2),

j)

12.4.8;

k)

12.4.9.

13.3.2.4

13.3.2.2.

0—5

30 “

60

8
2

16

10 X.

23

60*40—2017

14

14.1

8

8.0 8/ / — 4.0 8/ .

12.

14.2

()

) —);

a)

():

(. U_m 2 4).

b)

();

c)

();

d)

(-

)

10 %;

e)

().

12.5

12.4.4.

14.3

12.4.1 14.4
12.5.

14.4

- a) $\begin{array}{c} >0 \\ 10 \end{array}$ 12.4.3
12.4.4;
b) $\begin{array}{c} \text{tg } 5 \\ - \end{array}$ 12.4.5;

- c) $\begin{array}{c} 12.4.6 \\ 12.4.4 \end{array}$
d) $\begin{array}{c} \text{d)}: \\ 12.4.7 \end{array}$
e) $\begin{array}{c} 12.4.4 \\); \\ 0 \end{array}$
f) $\begin{array}{c} 12.4.8: \\ 12.4.9. \end{array}$

4.

15

15.1

- 4.0 $\begin{array}{c} 8/ \\ 12. \end{array}$

 $\begin{array}{c} 8,0 \\ / \end{array}$

8

15.2

- $(\quad),$
)
)
1
2
 U_m
($1 \quad 2$ 4);

)–d):

60*40—2017

3

b)

14.2.

2.5 /

c)

d)

15.3

15.4.1 15.4.2.

5

).

) —) 15.4.2

15.4

15.4.1

12.4.1.

15.4.2

a)

b)

12.4.4;

12.4.6;

c)

12.4.4:

•

•

d);

d)

12.4.7;

e)

f)

);

G.

1

).

2

f)

)

G.

()

4.

12.4.8.1.

16

16.1

16.2

/

16.3.

16.2.

16.3.

16.2

60229 () 5).

16.3

10

4.

 U_0

24

(*),

, ,

20—300

1

.

1—

		*	
			S
()	70	130 ^{1»}	
()	80	160 ^{1»}	
(XLPE) ()	90 90	250 250	
(HEPR)	90	250	
()		()	20 *

60*40—2017

2—

	()	.
(PVC)	ST, ST ₂	80 90
{ }	ST _a ST ₇	80 90

3— tg 6

(. 4.2}			EPR.HEPR	XLPE
tg 6 "4	10	10	50	10 ¹
(XLPE).				
,	tg	—50 10 ¹⁴ .		

4—

*	*	0	*	*	-	19	-	-	-
-	-	-	-	9.3. 2.5V ₀	9.2 12.4.4. 1.5U _w	12.4.5.	-	-	-
...	"	"	"				12.4.6. 2l/w	10.12. 12.4.7 13.2 S	12.4.7. 2.SU*
1	2	3	4)	5 ¹ >	6 ¹ >	7 ¹ >	8 ¹ >	'>	2>
45	47	52	26	65	39	26	52	250	65
60	69	72.5	36	90	54	36	72	325	90
110	115	123	64	160	96	64	128	550	160
132	138	145	76	190	114	76	152	650	190
150	161	170	87	218	131	87	174	750	218
12.4.1.									
2>									
16.3.									

5—

(. 4.2 4.3)								
			EPR	HEPR	XLPE	ST,	ST ₃	ST ₇
;	1'							
(-)); d) ()	-	X X — X —	X X — X —	X X X X —	X X — X —	X X — X X	X X — X —	X X — X X

5

{ .4.2 4.3}									
			EPR	HEPR	XLPE	ST,	ST ₂	ST ₃	ST _T
)						X	X		
)						X	X		
-	-	-	X	X	-	X	X	-	-
-	-	-	X	X	X	-	-	-	-
2*	-	X	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	X	X
X	X	-	-	-	X	-	-	X	X
-	-	-	-	X	-	-	-	-	-
-	-	-	-	X	-	-	-	-	-

')

, ,

2*

— — « » : — * —

—

()

(.4.2)					XLPE	EPR	HEPR
-	•	70	80	90	90	90	90
60811-1-1 ¹¹ (9.1):	/ ² % 10,0 300	12,5 350	12,5 200	4,2 200	8,5 200		
(8.1):	60811-1-2 ¹)						
•	*	100	110	135	135	135	135
-	*	12	± 2	± 3	13	13	13
-	240	240	168	168	168	168	168
)							
)	2*, ,						
)							
)	2*, ,						
(55±2) / ²							
60811-1-2 ¹¹ (8.2):	*						
-	,						
-							
-							
127							
11							
40							

60*40—2017

6

(. 4.2)					XLPE	EPR	HEPR
a)	²¹ , :	%	—	—	—	130 ±30	±30
b)		%					

1*
2> — , , , , , , ,

7—

()

(. 4.3)			ST,	ST ₂	ST ₃	ST _T
60811-1 -l ¹) (-	9.2):	/ 2	12.5	12.5	10,0	12.5
•		%	150	150	300	300
60811-1-2 ¹) (8.1):		"	100	100	100	110
•		•	±2	±2	±2	±2
•			168	168	240	240
)	²¹ , :	/ 2	12.5	12.5	—	—
)		%	±25	±25		
)	²¹ , :	%	150	150	300	300
)		%	±25	±25	—	—
60811-3-11* (-	8.2):	,	80	90	—	110
•		*	±2	±2		±2
60811-1-3 ¹ >	(11):	*			80	80
•		*	—	—	±2	±2
•			—	—	5	5
•			—	—	5	5
•	,	%	—	—	3.0	3.0
11	,	,	,	,	,	,
21	—	,	,	,	,	,
.
.

8 —

»

(. 4.2)				XLPE	EPR	HEPR
69811-2-11) (6): - () -	%				0.025 0.030 24	0.025 0.030 24
60811-2-1' > (9): • - • • - , - , - ,	*	—	—	200 13 15 20 175 15	250 13 15 20 175 15	250 13 15 20 175 15
60811-1-3 ¹ : (10): - L - - • • ,	*	200 100 ±2 6 4.5	200 115 12 6 4.5	200 130 13 6 4.5	— — — — —	— — — — —
60811-1-3 ¹ (8): - ,	r/CM ^J	—	0.94	—	—	—
(): • IRHD ² .						
12.5.15) 150- ,	/ 2					4.5

9 —

(. 4.4)		ST,	ST ₂
60811-3-2" (- 8.2): : - - - •	" ● / 2	— — — —	100 12 158 1.5

60°40—2017

9

()

.1

5—10 * ,

(5 '),

.2

.2.1

()

.2.2

5

2 * .

TC_{1s}

.1):

2 ^ 1

1,

()

()

.2.

()

2 2

2 * .

(8).
.2.3

(20115)* .

(.1)

5—10 *


1.

1.2 3:

TC_{1s}

-
-
-
-

60*40—2017



60840—2017

.3.1 1:

.2.

8

TC_{1s}

1

?1

2

5

± 1 %.

.3.2 2:

.3.2.1

.2.

.3.2.2

60853-2

60287-1-1,

60°40—2017

()

2.3 4. (),);
 - , ,
 7.6 5. ().

$$\begin{array}{r}
 2.449 = 2.45 \\
 2.449 \quad 2.4 \\
 2.453 \ll 2.45 \\
 2.453 \quad 2.5 \\
 25.0478 \bullet 25.048 \\
 25.0478 * 25,05 \\
 25.0478 \quad 25.0
 \end{array}$$

()

12,14 15

1.

4.0 /	8,0 8/ 13.1 13.2.
-------	----------------------

4.0 /	8,0 / 13.1 13.3.
-------	---------------------

2.

.1—

		12.1	14.1	15.1
		12.2	14.2	15.2
		12.4	14.4	15.4
d		12.4.1	12.4.1	12.4.1
		12.4.3	12.4.3	—
		12.4.4	12.4.4	12.4.4
f	tg 8	12.4.5	12.4.5	—
9		12.4.6	12.4.6	12.4.6
h	[i])	12.4.4 12.4.4		12.4.4 12.4.4
i		12.3.7	12.4.7	12.4.7
j	[o])	12.4.4 12.4.4		12.4.4 12.4.4
X		G	—	G

60*40—2017

. 1

1		12.4.8	12.4.8	12.4.8.1
m	-	12.4.9	12.4.9	-
	-	12.5	12.5	-

. 2 —

8.0 /
4.0 /

		13.1
		13.2
		13.2.1
d		13.2.2
		13.2.3
f		13.2.4
g		13.2.5
h		13.2.6

. — ,

8.0 /
4.0 /

	,	13.3
b	,	13.3.1
	,	13.3.2
d		13.3.2.1
		13.3.2.2
f	,	13.3.2.3
g		13.3.2.4

()

150

D.1)].

0.1)].

8. D,

$$(\cdot, 0.1) \rangle).$$


50

25

100


30

D.1).



— экран по изоляции, 2 — экран по жиле; A, D — электроды тока, B, C — электроды напряжения

) —



)—
D.1—

$$RMO-TJT = \frac{1}{21} \quad 1 \quad 1$$

Lg
D_c
—

, * (D.2)

L
D

()

.1

6

12.4

14.4.

12.4.3.

50

6

10

(.1)

.2

5


(20 110) *

1
24
10

(.1).

5 — 10 *

100 *

— 6
2
16)—
.1—
:2—
:J—

60 —2017

1

F
()


F.1

F.2
R2.1

200 10

50—120

F.1.




180°.

F.2.2
50 /

0.5 /


F.3
F.3.1
200
F.2.

60*40—2017



F.2.

F.3.



F.3.2

0.5 /

6

G.1

, 8 , () .

G.2

G.3 G.4

G.4 ,
12.4.6.

). 12.4.2, 2.

G.3

, 20 « — »
15—20 * ,
5 . 10 * ,
, 12 .
10 * , 30

G.4

G.4.1

G.4.2

G.4.3

G.4.3.1

G432

G1

60*40—2017

60230.

G.1—

1,				
	i 3	> £ 10 ²	s	>3 £ 10 ²>
250 325	60	60	30	30
325 750	60	75	30	37.5

8 4.

2|

s3 .

G.5

G.4

()

.1

(HEPR).

.2

48


.2.1

48

a)

b)

.1.



.1 —

20

4

48

.2.2

.2.1.

a)

b)

V-


.2);

.2).

4

48.

60*40—2017



)
2—

)

V-

.2.3

16 .

(20 ± 2) * .

3 .

.2.4

,
(IRHD).

()

.1

1 60060-1	—	*
1 60183	—	*
IEC 60228	MOD	22483—2012 « , »
1 60229:2007	—	*
1 60230	MOD	53354—2009 « »
IEC 60287-1-1:2006	IDT	60287-1-1—2009 « - . 1-1. (100-) »
IEC 60332-1-2	IDT	IEC 60332-1-2—2011 « 1-2. 1 »
1 60811-1-1:1993		1 60811-1-1—2011 « »
IEC 60811-1-2:1985		IEC 60811-1-2—2011 « 1-2. »
1 60811-1-3:1993		IEC 60811-1-3—2011 « 1-3. »
1 60811-1-4:1985		IEC 60811-1-4—2011 « 1-4. »
> 60811-2-1:1998		IEC 60811-2-1—2011 « 2-1. »
1 60811-3-1:1985		1 60811-3-1—2011 « »
! 60811-3-2:1985		IEC 60811-3-2—2011 « »

60*40—2017

1

IEC 60811-4-1:2004	IDT	IEC 60811-4-1—2011 « » (TGA). 4-1.
IEC 60885-3	—	
ISO 48		

• 1DT—
• MOD—

- (1) IEC 60287 (all parts) Electric cables — Calculation of the current rating
 ()
- (2) IEC 60853-2 Calculation of the cyclic and emergency current rating of cables — Part 2: Cyclic rating of cables greater than 18/30 (36) kV and emergency rating of cables of all voltages
 ()
 2.
 18/30 (36)
]
- (3) IEC 61443 Short-circuit temperature Bmits of electric cables with rated voltages above 30 kV ($L_m = 36$ kV)
 ()
 30 { $U_m = 36$ }]
- (4) Electra No. 128. Guide to the protection of specially bonded cable systems against sheath overvoltages. January 1990. pp. 46—62
 () no
 . Electra. 126. 1990. . 46—62)
- (5) Electra No. 141. Guidelines for tests on high voltage cables with extruded insulation and laminated protective coverings. April 1992. pp. 53—61
 () no
 . Electra, 141, 1992. . 53—61)
- (6) Electra No. 157. CIGRE Technical Brochure: Accessories for HV extruded cables. December 1994. pp. 84—89
 () CIGRE:
 Electra. 157, 1994. . 84—89)
- (7) Electra No. 173, After laying tests on high-voltage extruded insulation cables systems. August 1997, pp. 32—41
 () . Electra.
 173. 1997, . 32—41)
- (8) Electra No. 205, Experiences with tests after installation on the main insulation of polymeric (E)HV cable systems. December 2002. pp. 31—33
 () . Electra. 205. 2002, . 26—36)
- (9) Electra No. 227. Revision of qualification procedures for extruded high voltage AC underground cable systems. August 2006, pp. 31—37
 () . Electra.
 227. 2006. . 31—37)
- (10) CIGRE Technical Brochure 303: Revision of qualification procedures for extruded (extra) high voltage ac underground cables: CIGRE Working Group 1-06:2006
 () CIGRE 303:
 : ()
 CIGRE 1-06: 2006)

60640—2017

621.315:006.354

29.060.020 49

*

9—2017/25

20.09.2017 20.10.2017 60 * 64Vg.
 6.51. 6.33. 24 » ». 2292.

« *. 116419. , . 11.
www.jurieudalru y-book@mail.ru

« ». 123001. .. 4.
www.9oslmfo.ru mfo@9osbnfo.ru